


MARKS

<code>``code``</code>	code												
<code>**bold**</code>	bold												
<code>//italic//</code>	<i>italic</i>												
<code>__underline__</code>	<u>underline</u>												
<code>""_raw_""</code>	<code>_raw_</code>												
<code>= title 1 =</code>	title 1												
<code>== title 2 ==</code>	title 2												
<code>=== title 3 ===</code>	title 3												
<code>+++ numbered +++</code>	1.1.1. numbered												
<code>[txt2tags.jpg]</code>													
<code>[ABC www.abc.com]</code>	ABC (hyperlink)												
<code>abc</code> <code>% comment</code> <code>xyz</code>	abc xyz												
<code>abc</code> <code><tab>quote</code> <code>xyz</code>	abc quote xyz												
<code>- item</code> <code>- item</code> <code>- sub item</code>	• item • item • sub item												
<code>+ item</code> <code>+ item</code> <code>+ item</code>	1. item 2. item 3. item												
<code>: term</code> <code>definition</code> <code>: term</code> <code>definition</code>	term definition term definition												
<code>---</code> <code>verbatim</code> <code> **block**</code> <code>---</code>	verbatim **block**												
<table border="1"> <tr> <td> tit 1 tit 2 </td> <td>tit 1</td> <td>tit 2</td> </tr> <tr> <td> c1 c2 </td> <td>c1</td> <td>c2</td> </tr> <tr> <td> c3 c4 </td> <td>c3</td> <td>c4</td> </tr> <tr> <td> c5 + c6 </td> <td colspan="2">c5 + c6</td> </tr> </table>	tit 1 tit 2	tit 1	tit 2	c1 c2	c1	c2	c3 c4	c3	c4	c5 + c6	c5 + c6		
tit 1 tit 2	tit 1	tit 2											
c1 c2	c1	c2											
c3 c4	c3	c4											
c5 + c6	c5 + c6												

OPTIONS

<code>-t, --target=TYPE</code>	html, xhtml, sgml, tex, lout, man, mgp, moin, pm6, txt
<code>-i, --infile=FILE</code>	Input file ("-” for STDIN)
<code>-o, --outfile=FILE</code>	Output file ("-” for STDOUT)
<code>-H, --no-headers</code>	No header, title nor footer
<code>--encoding=ENC</code>	Encoding: utf-8, iso-8859-1, etc
<code>--style=FILE</code>	HTML CSS file
<code>--css-sugar</code>	Insert DIV tags for CSS
<code>--css-inside</code>	Insert CSS inside output file
<code>--toc</code>	Add Table of Contents (TOC)
<code>--toc-level=N</code>	Set maximum TOC level
<code>--toc-only</code>	Show TOC
<code>-n, --enum-title</code>	Enumerate all titles
<code>--mask-email</code>	Hide emails from spam robots
<code>-C, --config-file=FILE</code>	Read config from external file
<code>--dump-config</code>	Show input file config
<code>-V, --version</code>	Show program version
<code>--no-OPTION</code>	Turn OFF this option

MACROS

<code>%%Date</code>	The conversion date / modification time
<code>%%Mtime</code>	Default: %Y%m%d %Y (year) %m (month) %d (day) %H (hour) %M (min) %S (sec) %c (full) %A %a (weekday) %B %b (month name) %%date(%Y-%m-%d %H:%M)
<code>%%Infile</code>	The input/output file path
<code>%%Outfile</code>	Default: %f %f (file) %e (ext) %d (dir) %p (path) %F (file w/o ext) %D (parent dir) %%outfile(%D :: %F :: %e)
<code>%%TOC</code>	User specified TOC location %%toc

SETTINGS

<code>%!Target</code>	Same as --target %!target: html
<code>%!Encoding</code>	Same as --encoding %!encoding: iso-8859-1
<code>%!Style</code>	Same as --style %!style: abc.css
<code>%!Options</code>	Default command line options %!options: -n --toc
<code>%!PreProc</code>	Input search & replace filter %!preproc: JJS "John J Smith"
<code>%!PostProc</code>	Output search & replace filter %!postproc(html): @@
<code>%!IncludeConf</code>	Same as --config-file %!includeconf: myconfig.t2t

INCLUDE

<code>%!Include: F</code>	Include file F as txt2tags file
<code>%!Include: `F`</code>	Include file F as verbatim block
<code>%!Include: "F"</code>	Include file F as raw block

OTHER

Headers	First 3 lines
Config	Comments after Headers
Body	From first text line to the end
RC config file	~/txt2tagsrc (unix, mac), _t2trc (win)
Anchor	=title=[anchor] ... [link #anchor]

SAMPLE INPUT FILE

Lord Of The Rings J. R. R. Tolkien Last Update: %%mtime(%c)
<pre> %!target: html %!options(html): --css-sugar --style lotr.css They walked, they fought, they won. **Hooray!** </pre>